

PENTAX | Total Surveying Solutions

R-2800N Series

R-2801N | R-2802N | R-2803N | R-2805N



- + Long EDM range measuring distance in reflectorless up to 800 m and in prism mode up to 4,000 m
- + Large internal memory: 60,000 points
- + Dual display as a standard equipment
- + Easy transfer to a PC via SD card, USB mini and RS-232C data port
- + Pre-loaded versatile software functions
- + Dual battery system for long time use
- + Bluetooth Class1 Long Link: 100 m

TI Asahi Co.,Ltd
Aiming at the future together!

PENTAX | Total Surveying Solutions **R-2800N Series**

R-2801N | R-2802N | R-2803N | R-2805N

- + Long EDM range:
reflectorless up to 800 m
and in prism mode up to 4,000 m
- + Large internal memory:
60,000 points
- + Dual display
- + Easy transfer to a PC via SD card,
USB mini and RS-232C data port
- + Pre-loaded versatile
software functions
- + Dual battery system
for long time use
- + Bluetooth Class1
Long Link: 100 m



TI Asahi Co.,Ltd
Aiming at the future together!

Technical Specifications R-2800N Series Total Station

Model		R-2801N	R-2802N	R-2803N	R-1505N	
Telescope	Image			Erect		
	Magnification			30 x		
	Effective Aperture			45 mm		
	Resolving Power			3.0"		
	Field of View			1°20'		
	Minimum Focus			1.0 m		
	Focus			Manual		
	Laser Class		Visible Laser: Class IIIa (Reflectorless, sheet) / Class I (Prism)			
	Measurement Range	(Good condition) *3				
		Reflectorless *1			1.5 m ~ 800 m	
Reflector Sheet *2				1.5 m ~ 800 m		
Mini Prism				1.5 m ~ 800 m		
1P				1.5 m ~ 4,000 m		
3P				1.5 m ~ 5,000 m		
Accuracy	Prism		± (2 + 2 ppm x D) mm			
	Reflector Sheet		± (3 + 2 ppm x D) mm			
	Reflectorless		2.0 m ~ 200 m: ± (3 + 2 ppm x D) mm			
			200 m ~ 300 m: ± (5 + 2 ppm x D) mm			
		300 m ~ 500 m: ± (10 + 2 ppm x D) mm				
		500 m ~ 800 m: ± (20 + 10 ppm x D) mm				
Measurement Time *4	Minimum Count		0.1 mm (Fine mode), 1 mm (Normal mode), 10 mm (Track mode)			
	Repeat Meas.	Fine (0.1 mm)	Prism / Ref. Sheet 3.0 sec., Ref. less 3.0 sec. (over 300 m 5.0 sec.)			
		Normal (1 mm)	Prism / Ref. Sheet 2.0 sec., Ref. less 2.0 sec. (over 300 m 4.0 sec.)			
	Initial Meas.	Track (10 mm)	Prism / Ref. Sheet 0.4 sec., Ref. less 0.4 sec. (over 300 m 0.4 sec.)			
		Fine (0.1 mm)	1.5 ~ 300 m 3.5 sec., over 300 m ~ 13 sec.			
	Normal (1 mm)	1.5 ~ 300 m 2.4 sec., over 300 m ~ 12 sec.				
Angle Measurement	Track (10 mm)	1.5 ~ 300 m 2.5 sec., over 300 m ~ 12 sec.				
	Measuring Method		Absolute rotary encoder			
	Detection Method		Vertical / Horizontal angle			
	Minimum Count		2 sides			
Accuracy (ISO17123-3)		1"	2"	3"	5"	
Compensator			2 axis			
Compensator range			3' 30"			
Tangent Screw			1 Speed / Clamping (< 30°)			
Sensitivity of Vials	Plate Level		30"/1 div. (electrical)			
	Circular Level		8/2 mm			
Plummet			Visible Laser, ± 0.5 mm (instrument height 1.5 m)			
Base			Detachable			
Dust and Water Protection			IP55 (instrument only)			
Ambient Temperature			-20°C ~ 50°C / -4°F ~ 122°F (Working range)			
Tripod Thread			5/8" x 11			
Dimensions/Weight	Dimensions		183 (W) x 342 (H) x 167 (L) mm			
	Weight (incl. Battery)		5.4 kg			
Carrying Case			440 (W) x 370 (H) x 275 (L) mm / 3.9 kg			
Battery Pack	Power Source		Li-ion 3,350 mAh x 2 = 6,700 mAh (hotswap)			
	Operation Time		Continuous approx. 10.0 hrs (ETH+EDM) with approx. 2.5 hrs of charging time			
	Weight		5,400 g			
Battery Charger and AC Adapter	Input Voltage (AC05)		AC 100 ~ 240V			
	Output Voltage (BC05)		DC8.4V			
Data Process	Data Recording Method		Internal Memory			
	Capacity / Coordinates Data		Up to 2GB / 60,000			
	Special Function		PowerTopoExpress 2			
	I/F		RS-232C, SD CARD, USB mini, Bluetooth (Class1)			
Display / Keyboard	Display Type		Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels			
	Quantity		2			
	Keys		22 each (12 numeric / 5 function / 5 special)			
Display Back Light			Intensity settings: 10 steps			
Laser Pointer			Yes			
Date Clock			Yes			

- *1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment.
The measurement range of reflectorless is determined by the white side of the Kodak Gray Card.
- *2 Reflector sheet: Genuine Reflector sheet
- *3 The measurement range may vary by conditions of the environment.
Normal conditions: 20km visibility with slight shimmer
Good conditions: 40km visibility with overcast, no heat, no shimmer and moderate wind.
- *4 EDM measuring time is determined in good conditions. It may take longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode.

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
 Japan Surveying Instruments Manufacturers' Association
 Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

